

Kilogaussmeter: IDR-329



Features:

- Contour case
- High range DC static Kilogaussmeter
- Portable
- Reference magnet included
- Battery powered (battery included)
- Analog output: +/- 200mV DC FS
- Two years parts & labor warranty
- 3 1/2 digit bipolar display
- Optional 9V DC adaptor
- Easy to use
- 3% error guarantee
- Low cost
- Made in the U.S.A.
- Resolution @ Scale 20: 10 mG, @ Scale 200G 0.1G, @ Scale 2KG: 1G & @ Scale 20KG: 10G

Typical applications:

- Classify Magnets, etc.
- Testing Audio Speaker Magnet
- Analyze Magnetic Circuit and Components
- Measure Residual Magnetic Fields

Specifications:

Range settings: 20 G, 200 G, 2KG & 20KG

Bandwidth: 68 Hertz @ 3 dB

Case Material: High Impact Styrene

Dimensions: 5.8"×3.6"×2.5"

Power Consumption: 200mW

Battery Life: At least 10 hours with 9V alkaline

Weight: 11 oz (312 grams)

Axial Probe: Optional Hall effect probe w/3.5' shielded cable

Transverse Probe: Optional Hall effect probe w/3.5' shielded cable



Integrity Design

& Research Corporation.

Electromagnetic Measurement

IDR-329-T: Kilogaussmeter W/Transverse Probe

IDR-329-A: Kilogaussmeter w/Axial Probe

IDR-329-T-A: Kilogaussmeter w/Axial & Transverse Probe

IDR-310-T: Transverse Replacement Probe

IDR-310-A: Axial Replacement Probe

IDR-311-T: Ultra Thin Transverse Probe

IDR-329-T-UL: Kilogaussmeter W/ Ultra Thin Transv. Probe

182 Browns River Rd

Essex Jct., VT 05452

Telephone: (802) 872-7116

Toll Free: (800) 719-2315

Facsimile: (802) 872-7115

<http://www.gaussmeter.info>

<http://www.integritydesign.com>